

Sonus SBC 5100™ Session Border Controller

For years, the world's largest service providers and enterprises have relied on Sonus session border controllers (SBCs) for secure SIP-based communications. Now, smaller service providers and enterprises have a reason to rejoice: the Sonus SBC 5100. The SBC 5100 delivers many of the industry-leading capabilities of the Sonus SBC 5200—robust security, flexible SIP session routing & policy management, media transcoding—at a more attractive price/performance point for Tier 2/3 service providers and medium-to-large enterprises (250 to 10,000 concurrent sessions). With high-end features you won't find in other "mid-sized" SBCs, the SBC 5100 allows regional service providers and medium-to-large enterprises to deliver a world-class communications experience designed for their world.



System Capabilities

- > Sessions
 - 10,000 sessions (SIP and/or H.323)
 - 10,000 calls
 - 10,000 transcoded sessions (based upon codec type)
 - RTP sessions scale 1:1 with RTP sessions
- > Call Set-Up
 - Maximum call setup rate: 150 cps
- > Registrations
 - Maximum new registration/sec: 400
 - Maximum refreshes/sec: 1,700 per second
 - Total registered end point support: 100,000; up to 10,000 NAT'd end points
- > Encryption
 - iMaximum number of TLS sessions: 10,000
 - TLS set-up rate: 50 cps w/o mutual authentication
 - iMaximum # of IPsec tunnels: 2,048 (4,096 IPsec SAs)
 - iIPsec (IKE) setup rate: 50 cps
 - Maximum # SRTP sessions: 10,000

Media Services

- > Transcoding up to 10,000 concurrent calls: G.711, G.726, G.729A/B, G.723, iLBC, G.722, AMR-NB,
- > AMR-WB, EVRCB0, EVRC0
- > Wireline, wireless, wideband and clear channel codec pass through
- > T.38 compliant fax relay or fall back to G.711
- > VAD, Silence Suppression, Dynamic Jitter Buffer, Fax/ Modem Detection, DTMF/Tone Relay/RFC2833/ RFC4733 interworking
- > NAT/NAPT on media
- > DTMF Trigger Detection and Notification
- > Generic audio codec relay
- > Tones & Announcements
- > Local Ring Back Tone (LRBT) support with centralized PSX Policy Server
- > RTP inactivity monitoring
- > Video codec relay

Redundancy

- > 1:1 Redundant Systems for Service Availability
- > 1:1 Redundant Management/ Control Ports

Management Capabilities

- > Graphical based wizards for ease of configuration
- > Secure embedded web-based management GUI
- > Sonus CLI, SSH
- > Centralized support by Sonus Insight EMS
- > SNMP V2 status and statistics
- > Local logging of events, alarms, and traps; Call trace
- > Sonus DSI Level 0 support for storing CDRs; RADIUS accounting records
- > Live Software Update (LSWU)

Signaling

- > Back to Back User Agent (B2BUA)
- > SIP, SIP-I/ SIP-T, SIP/H.323; Sonus Gateway to Gateway Signaling
- > SIP protocol normalization/ protocol repair; SIP message manipulation
- > NAT/NAPT on signaling

Protocol Support

- > IPv4, IPv6, IPv4/IPv6 interworking
- > SSH; sFTP
- > SNMP; NETCONF; NTP
- > HTTP/HTTPS
- > RTP/RTCP
- > UDP, TCP
- > DNS, ENUM

Routing/Policy

- > Embedded policy/ routing engine
- > Optional centralized policy/routing via Sonus Centralized Policy Server (PSX Server) using Diameter+
- > Screening, blocking, routing, presentation, call type filters
- > Route prioritization
- > Leading digit routing; International routing; URI based routing
- > Digit/parameter manipulation
- > E911 support; Priority Call handling

Security

- > Session-aware firewall; Topology hiding
- > Line rate DoS/DDoS and Rogue RTP protection
- > Line rate malformed packet protection
- > TLS, IPsec (IKEV1) for signaling encryption
- > Secure RTP/RTCP for media encryption

Quality of Service (QoS)

- > Bandwidth management
- > Call admission control (CAC) per trunk group, per zone
- > Per call statistics
- > TOS/ COS packet marking

Packet Network Time Source

- > Network Time Protocol (NTP) per RFC-1708

Hardware Specifications

Front Panel

- > Status Indicators Front Panel LEDs
 - Status
 - Critical
 - Major
 - Minor
 - User
 - Location
- > Single USB V2.0 interface

Rear Panel

- > Management Ports
 - Two (single active, single passive) 10/100/1000 Ethernet RJ-45 ports
- > Media Ports
 - Two 1 Gbps Ethernet fiber or copper via SFP
- > High Availability Ports
 - Two 1 Gbps Ethernet multimode fiber via SFP
- > Single Field Service port with RJ45 connector
- > Locator LED
- > Alarm port with DB15 connector
- > Single serial craft DB9 port

Memory

- > 12 GB of RAM

Chassis

- > 2U, rack mount
- > Inches: 17.5" Wide x 3.5" High x 21" Deep
- > Centimeters: 44.5 Wide x 8.8 High x 53.3 Deep
- > Optional mounting brackets for 19" or 23" rack

Chassis Mounting Options:

- > 19" or 23" Adjustable Brackets

Storage

- > 80 GB of Solid State Disk (SSD) storage

Hardware Specifications (cont.)

AC Power Option

- > RMS Input Voltage
 - Minimum 90 VAC
 - Nominal 100-240 VAC
 - Maximum 264 VAC
- > RMS Current
 - Low Line: 6.5A
 - High Line: 3.1A
- > Input Frequency
 - Minimum: 47 Hz
 - Nominal: 50/60 Hz
 - Maximum: 63 Hz

DC Power Option

- > Input: -40 to -72 VDC Redundant Inputs
- > Nominal Consumption: 11.6A
- > Peak Consumption: 14.5A
- > Number of power supplies, standard : 1 (Redundant dual power supply optional)

Operating Altitude

- > 6,000 ft. (1,800 m.)

Heat Dissipation

- > Fully-Populated Maximum:
 - 641 Watts
 - 2186 BTU per Hour
- > Replaceable Filter

Weight Maximum Fully Populated

- > 50 lbs. (22.68 kg)

Environmental

- > 5 to 40° C Operating
- > -5 to 55° C Short Term
- > 5 to 90% Non-Condensing Operating Humidity

Regulatory Compliance

EMI/EMC

- > CFR47 Part 15 Class A - United States
- > ICES-03 - Canada
- > CISPR22 Class A - International Standard
- > VCCI Class A - Japan
- > AS/NZ 3548 Class A - Australia & New Zealand
- > CNS 13438; Taiwan (BSMI)
- > ETSI EN 300 386 Electromagnetic Compatibility (EMC) requirements - Europe
- > ETSI EN 300 386-2 Electromagnetic Compatibility (EMC) requirements
- > EN 55024
- > EN 55022 Class A emissions
- > EN 6100-4-2; ESD Immunity
- > EN 6100-4-3; Radiated immunity
- > EN 6100-4-4; EFT/B Immunity
- > EN 6100-4-5; Surges
- > EN 6100-4-6; Conducted Immunity
- > EN 6100-4-11; Voltage Dips and Interruptions
- > EN 6100-3-3; Flicker
- > EN 6100-6-2; Harmonics

Central Office Standards

- > DC Systems - SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE
- > AC Systems - SR-3580 NEBS Level 3
 - GR-1089-CORE
 - GR-63-CORE

European Environmental Standards

- > ETSI EN 300 019-1-0 Part 1-0: Classification of environmental conditions, Introduction
- > ETSI EN 300 019-1-1 Class 1.2 Part 1-1: Classification of environmental tests; Storage
- > ETSI EN 300 019-2-1 Storage Class 1.2
- > ETSI EN 300 019-1-2 Class 2.3 Part 1-2: Classification of environmental conditions; Transportation
- > ETSI EN 300 019-2-2 Transportation Class 2.2
- > ETSI EN 300 019-1-3 Class 3.2 Part 2-3: Classification of environmental conditions; Stationary use at weather-protected locations
- > ETSI EN 300 019-2-3 V2.2.2 Stationary use at weather-protected locations Class 3.1E

Safety

- > UL 60950-1 - United States
- > CAN/CSA-C22.2 NO. 60950-1-03 - Canada
- > IEC/ EN 60950-1 - European Union
- > AS/NZS 60950:2000 - Australia & New Zealand
- > NOM 019 - Mexico
- > IEC 60950; IECCEB CB Scheme - International

To learn more, call your Sonus sales representative or visit us online at www.sonusnet.com.

Table 1. Estimated Power Consumption (all power measurements taken with fans running high)

			AC Low Line		AC High Line		DC	
			Minimum: 90 Vrms Nominal: 100-120 Vrms Maximum: 140 Vrms		Minimum: 180 Vrms Nominal: 200-240 Vrms Maximum: 264 Vrms		Minimum: 40 Vdc Nominal: 48 Vdc Maximum: 60 Vdc	
	SPS100	SPS100DB	Amps	Watts	Amps	Watts	Amps	Watts
SBC 5100	0	0	4.5	402	2.2	393	10.0	403
	1	0	5.5	485	2.4	468	11.7	472
	1	1	6.3	562	3.1	546	13.2	560
	1	2	7.1	633	3.4	619	14.5	617



Sonus Networks, Inc. 4 Technology Park Drive Westford, MA 01886 1.978.614.8100

The content in this document is for informational purposes only and is subject to change by Sonus Networks without notice. While reasonable efforts have been made in the preparation of this publication to assure its accuracy, Sonus Networks assumes no liability resulting from technical or editorial errors or omissions, or for any damages resulting from the use of this information. Unless specifically included in a written agreement with Sonus Networks, Sonus Networks has no obligation to develop or deliver any future release or upgrade or any feature, enhancement or function.

Copyright © 2012 Sonus Networks, Inc. All rights reserved. Sonus Networks is a registered trademark and SBC 5100 is a trademark of Sonus Networks, Inc. All other trademarks, service marks, registered trademarks or registered service marks may be the property of their respective owners.