

REMOTE MANAGEMENT

MONITOR AND CONTROL DATA CENTRE SYSTEMS FROM ANYWHERE



Tripp Lite remote management solutions for data centers give IT professionals unprecedented capabilities for monitoring and controlling critical infrastructure. Select UPS systems, PDUs and KVMs provide real-time data on power consumption, with the ability to monitor and control connected devices using a variety of platforms. Tripp Lite remote management solutions offer greater efficiency, reliability and security, so you can have greater peace of mind about your data center operations.



Powering and Connecting Your World

NETWORK MONITORING

Study trends in power usage and identify problem devices so you can maximise power efficiency and address issues proactively.

- Real-time remote monitoring of voltage, load levels and frequency
- Metering of input current per phase
- Bank and individual outlet-level monitoring
- Environmental monitoring with sensors that track temperature, humidity and security data

FLEXIBLE ACCESS

Connect to your UPS and PDU with browser-based or software-based platforms that best fit your systems.

Supported interfaces:

- HTML5 web via HTTP(S)
- Menu/CLI via SSH/Telnet
- SNMP (v1, v2, v3)
- SMTP, FTP, DHCP and NTP

ADVANCED MANAGEMENT TOOLS

Automatically reboot problematic devices and use remote KVM functionality for complete control of select computers and servers.

- Outlet power cycling (including individual outlets)
- Remote KVM (keyboard + video + mouse) control of up to 64 connected computers and servers from a browser-based platform
- Self-testing
- Device Configuration
- Automated notifications via email and SNMP trap
- Event logging
- Graceful shutdown in the event of a power interruption

REMOTE MANAGEMENT

Tripp Lite remote management solutions for data centres help prevent downtime and respond to network interruptions quickly – all while reducing the time and expense of on-site troubleshooting.

UPS



Tripp Lite Model	Description
Single-Phase	
SUINT3000RTXL2U	SmartOnline Double-Conversion UPS - 2U, USB, DB9, 230V, 3kVA, 2.5kW, On-Line
SUINT3000LCD2U	208/230V 3000VA 2.7kW Double-Conversion UPS - 10 Outlets, Extended Run, Card Slot, LCD, USB, DB9, 2U
SUINT2200LCD2U	208/230V 2200VA 1.98kW Double-Conversion UPS - 9 Outlets, Extended Run, Card Slot, LCD, USB, DB9, 2U
SUINT1500LCD2U	208/230V 1500VA 1.35kW Double-Conversion UPS - 6 Outlets, Extended Run, Card Slot, LCD, USB, DB9, 2U
SUINT1000LCD2U	208/230V 1000VA 900W Double-Conversion UPS - 6 Outlets, Extended Run, Card Slot, LCD, USB, DB9, 2U
SUINT3000LCD2UN	208/230V 3000VA 2700W Double-Conversion UPS - 10 Outlets, Extended Run, WEBCARDLX, LCD, USB, DB9, 2U
SUINT1000LCD2UN	208/230V 1000VA 900W Double-Conversion UPS - 6 Outlets, Extended Run, WEBCARDLX, LCD, USB, DB9, 2U
SUINT1500LCD2UN	208/230V 1500VA 1350W Double-Conversion UPS - 6 Outlets, Extended Run, WEBCARDLX, LCD, USB, DB9, 2U
USB-A Solutions	
SVX150KL	SmartOnline SVX Series 150kVA Modular, Scalable 3-Phase, On-Line Double-Conversion 400/230V 50/60 Hz UPS System
SU100KX2	SmartOnline 100kVA Modular 3-Phase UPS System, On-Line Double-Conversion International UPS
S3M100KX	SmartOnline S3MX Series 3-Phase 380/400/415V 100kVA 90kW On-Line Double-Conversion UPS
SVX210KL8P	SmartOnline SVX Series 210kVA N+1 Modular, Scalable 3-Phase, On-Line Double-Conversion 400/230V 50/60 Hz UPS System
SU120KX2	SmartOnline 120kVA Modular 3-Phase UPS System, On-Line Double-Conversion International UPS
SVX210KL7P	SmartOnline SVX Series 210kVA Modular, Scalable 3-Phase, On-Line Double-Conversion 400/230V 50/60 Hz UPS System
SVX120KL	SmartOnline SVX Series 120kVA Modular, Scalable 3-Phase, On-Line Double-Conversion 400/230V 50/60 Hz UPS System
SVX180KL	SmartOnline SVX Series 180kVA Modular, Scalable 3-Phase, On-Line Double-Conversion 400/230V 50/60 Hz UPS System
S3M160KXD	SmartOnline S3MX Series 3-Phase 380/400/415V 160kVA 144kW On-Line Double-Conversion UPS, Parallel for Capacity and Redundancy, Single & Dual AC Input
S3M200KX	SmartOnline S3MX Series 3-Phase 380/400/415V 200kVA 180kW On-Line Double-Conversion UPS
S3M160KX	SmartOnline S3MX Series 3-Phase 380/400/415V 160kVA 144kW On-Line Double-Conversion UPS
S3M100KXD	SmartOnline S3MX Series 3-Phase 380/400/415V 100kVA 90kW On-Line Double-Conversion UPS, Parallel for Capacity and Redundancy, Single & Dual AC Input
S3M120KXD	SmartOnline S3MX Series 3-Phase 380/400/415V 120kVA 108kW On-Line Double-Conversion UPS, Parallel for Capacity and Redundancy, Single & Dual AC Input
S3M120KX	SmartOnline S3MX Series 3-Phase 380/400/415V 120kVA 108kW On-Line Double-Conversion UPS
S3M200KXD	SmartOnline S3MX Series 3-Phase 380/400/415V 200kVA 180kW On-Line Double-Conversion UPS, Parallel for Capacity and Redundancy, Single & Dual AC Input

* Single-phase and 3-phase UPS systems with remote management capabilities and output under 100kVA models are also available.

Pulse Supply
909 Ridgebrook Road, Sparks, Maryland 21152, USA
TEL : +1-410-583-1701 FAX : +1-410-583-1704
E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/tripp-lite>



Powering and Connecting Your World

PDU



Tripp Lite Model	Description
Single-Phase	
PDUMH15HVATNET	2.4kW Single-Phase Switched Automatic Transfer Switch PDU, 2 200-240V C14 Inlets, 10 C13 Outputs, 1U, TAA
PDUMV20HVNETHX	3.2-3.8kW Single-Phase Switched PDU with LX Platform Interface, 200-240V Outlets (20 C13; 4 C19), C20/L6-20P, 0U, TAA
PDUMH15HVNET	2.3-2.9kW Single-Phase Switched PDU with LX Platform Interface, 200-240V (8 C13), C14, 200-240V Input, 2 m Cord, 1U Rack-Mount, TAA
PDUMH20HVNET	3.3-3.8kW Single-Phase Switched PDU, LX Platform Interface, 208/220/230/240V Outlets (8 C13), C20 / L6-20P Input, 2.4 m Cord, 1U Rack-Mount, TAA
PDUMV20HVNETHX2LX	3.3-3.7kW Single-Phase Switched PDU, LX Platform Interface, 208/230V Outlets (7 C13/1 C19), C20/L6-20P, 0U 1 m, TAA
PDUMV32HVNETHX	7.4kW Single-Phase Switched PDU with LX Platform Interface, 230V Output, IEC 309 32A Blue, 3 m Cord, 0U, TAA
PDUMH32HVNET	7.4kW Single-Phase Switched PDU, LX Platform Interface, 230V Outlets (16-C13), IEC-309 Blue 230V 32A, 3.6 m Cord, 2U Rack-Mount, TAA
3-Phase	
PDU3XEVS6G32B	22.2kW 3-Phase Switched PDU, LX Platform Interface, 220/230V Outlets (24 C13/6 C19), Touchscreen LCD, IEC 309 32A Red 380/400V, 0U, TAA
PDU3XEVS6RHWA	28.8kW 3-Phase Switched PDU with LX Platform, 220/230/240V Output, Hardwire, Touchscreen LCD, 0U, TAA
PDU3XEVS6G20	11.5kW 3-Phase Switched PDU - 24 C13 & 6 C19 Outlets, IEC 309 16/20A Red, 0U, Outlet Monitoring, TAA
PDU3XEVS6RHWB	28.8kW 3-Phase Switched PDU, LX Platform Interface, 220/230/240V Outlets (24 C13/6 C19), LCD, Hardwire 380/400/415V Input, 0U, TAA
PDU3XEVS6G63B	27.7kW 3-Phase Switched PDU, LX Platform Interface, 220/230V Outlets (24 C13/6 C19), Touchscreen LCD, IEC 309 63A Red 380/400V, 0U, TAA
PDU3XEVS6G32A	22.2kW 3-Phase Switched PDU - 12 C13 & 12 C19 Outlets, IEC 309 32A Red, 0U, Outlet Monitoring, TAA
PDU3XEVS6G63A	27.7kW 3-Phase Switched PDU - 12 C13 & 12 C19 Outlets, IEC 309 63A Red, 0U, Outlet Monitoring, TAA

KVM



Tripp Lite Model	Description
8- and 16-Port KVM	
B030-008-17-IP	NetDirector 8-Port 1U Rack-Mount Console HDMI KVM Switch with 43 cm LCD and IP Remote Access, Dual Rail
B072-016-1-IP	NetCommander 16-Port Cat5 KVM over IP Switch - 1 Remote + 1 Local User, 1U Rack-Mount
B072-008-1-IP	NetCommander 8-Port Cat5 KVM over IP Switch - 1 Remote + 1 Local User, 1U Rack-Mount
B070-008-19-IP	NetCommander 8-Port Cat5 KVM over IP Switch - 48 cm LCD, 1 Remote + 1 Local User, 1U Rack-Mount
B070-016-19-IP	NetCommander 16-Port Cat5 KVM over IP Switch - 48 cm LCD, 1 Remote + 1 Local User, 1U Rack-Mount
B020-U08-19-IP	NetDirector 8-Port 1U Rack-Mount Console KVM Switch with 48 cm LCD and IP Remote Access
B072-016-IP2	NetCommander 16-Port Cat5 KVM over IP Switch - 2 Remote + 1 Local User, 1U Rack-Mount
B064-016-02-IPG	NetDirector 16-Port Cat5 KVM over IP Switch - Virtual Media, 2 Remote + 1 Local User, 1U Rack-Mount, TAA
B072-016-IP4	NetCommander 16-Port Cat5 KVM over IP Switch - 4 Remote + 1 Local User, 1U Rack-Mount
B020-U16-19-IP	NetDirector 16-Port 1U Rack-Mount Console IP KVM Switch with 48 cm LCD
B070-016-19-IP2	NetCommander 16-Port Cat5 KVM over IP Switch - 48 cm LCD, 2 Remote + 1 Local User, 1U Rack-Mount
B064-008-01-IPG	8-Port Cat5 KVM over IP Switch with Virtual Media - 1 Local + 1 Remote User, 1U Rack-Mount, TAA
B064-016-04-IPG	NetDirector 16-Port Cat5 KVM over IP Switch - Virtual Media, 4 Remote + 1 Local User, 1U Rack-Mount, TAA
B064-016-01-IPG	NetDirector 16-Port Cat5 KVM over IP Switch - Virtual Media, 1 Remote + 1 Local User, 1U Rack-Mount, TAA
32- and 64-Port KVM	
B064-032-04-IPG	NetDirector 32-Port Cat5 KVM over IP Switch - Virtual Media, 4 Remote + 1 Local User, 1U Rack-Mount, TAA
B064-032-02-IPG	NetDirector 32-Port Cat5 KVM over IP Switch - Virtual Media, 2 Remote + 1 Local User, 1U Rack-Mount, TAA
B072-032-IP2	NetCommander 32-Port Cat5 KVM over IP Switch - 2 Remote + 1 Local User, 1U Rack-Mount
B072-032-IP4-K	NetCommander 32-Port Cat5 KVM over IP Switch - 4 Remote + 1 Local User, 16 USB Dongles, 1U Rack-Mount
B072-032-IP2-K	NetCommander 32-Port Cat5 KVM over IP Switch - 2 Remote + 1 Local User, 16 USB Dongles, 1U Rack-Mount
B072-032-IP4	NetCommander 32-Port Cat5 KVM over IP Switch - 4 Remote + 1 Local User, 1U Rack-Mount
B064-064-08-IPG	NetDirector 64-Port Cat5 KVM over IP Switch - Virtual Media, 8 Remote + 1 Local User, 2U Rack-Mount, TAA
B064-032-01-IPG	NetDirector 32-Port Cat5 KVM over IP Switch - Virtual Media, 1 Remote + 1 Local User, 1U Rack-Mount, TAA