

ErisTerminal® SIP Deskset

VSP715

The compact VSP715 SIP deskset comes with all the essential features you need to keep pace with your business and your budget. Installation is easy and cost-effective with Power over Ethernet (PoE) support, dual Ethernet ports and auto-provisioning. Two programmable buttons provide one-touch access to shared call appearances, ACD, paging and more. Manage multiple calls with advanced call handling features and support for up to two SIP lines/accounts. Support for the G.722 wideband codec for HD Audio means you'll enjoy superior voice quality too.



VSP715 Key Features

Advanced call handling

Impress customers with comprehensive call handling features that are compatible with hosted and open-source PBX platforms.*

Flexibility

With support for up to two SIP lines/accounts, you can manage multiple calls with advanced call handling features.

Intuitive design

You're in business with a user-friendly interface, large backlit display, three soft keys and navigational pad.

Full-duplex speakerphone

Finally, a speakerphone that can keep up with your calls. Increase participation by allowing parties on both ends to speak and be heard – at the same time – for conversations that are more true to life.

HD voice quality

With G.722 wideband codec support for HD audio, calls have never sounded so rich and life-like.

Dual Ethernet ports

Do more with dual Ethernet ports. Connect your desktop computer or laptop to the phone – no need for extra cabling.

Power over Ethernet (PoE)

With PoE support, you can locate the phones anywhere that's convenient - no AC outlets or complicated wiring required.

Three-year warranty

Enjoy peace of mind that comes with an industry-leading, standard three-year warranty. VTech also provides advance replacement on warranty claims using new, not refurbished, products.



Pulse Supply
909 Ridgebrook Road.
Sparks, Maryland 21152, USA

TEL : +1-410-583-1701
FAX : +1-410-583-1704
E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/vtech>

*Compatible with Broadsoft®, Genband™, Metaswitch Networks and Asterisk-based platforms.



Specifications, Weights and Dimensions

- Color: Black
- UPC: 735078034922
- Product dimensions (WxDxH):
BS: 6.09" x 8.60" x 5.59"
Corded HS: 8.09" x 1.99" x 2.05"
HS on BS: 6.09" x 8.60" x 6.77"
Footprint at 45 degree: 6.09" x 7.86" x 6.93"
- Product weight: 0.91 lbs.
- Giftbox dimensions (WxDxH):
8.89" x 3.94" x 6.30"
- Giftbox weight: 2.27 lbs.
- Master pack dimensions (WxDxH):
18.31" x 8.46" x 7.09"
- Master pack weight: 10.03 lbs.
- Quantity: 4

Interface

- Dual Ethernet ports: 10/100 Mbps
- Base power: AC adapter (optional) and Class 2 Power over Ethernet (PoE)

Display, Keys and Indicators

- 158 x 57 pixels (w x h) LCD resolution
- LCD backlighting (white)
- 3 soft keys
- 7 dedicated feature keys
- 2 programmable feature keys
- 4-way navigational pad
- Message waiting LED indicators

Audio

- Full-duplex base speakerphone
- HAC Receiver
- 2.5 mm corded headset jack
- HD Voice for receiver

Phone Features

- Supports up to 2 SIP account registrations
- Local phonebook up to 200 entries
- Phonebook import/export
- LDAP/Broadsoft® remote phonebook
- Call history up to 200 entries
- Shared Call Appearance (SCA)/ Bridged-Line Appearance (BLA)
- Do Not Disturb (DND)
- Busy lamp fields (BLF)

- 3-way local conference
- N-way network conference
- Call barring/blocking (block anonymous/blacklist)
- Dial plan/digit map
- Hotline
- Intercom
- Mute
- Redial
- 10 speed dial entries
- Call transfer: blind/attended
- Call hold
- Call park
- Call pick up
- Call forwarding: per-line basis (busy/always/no answer)
- Call timer (call duration)
- Caller ID
- Phonebook matching (incoming and outgoing calls)
- Multicast paging
- Multi-language support
- Automatic Call Distribution (ACD)

Customization

- Soft key configuration
- Custom startup and idle logo
- Web interface configuration (admin & user)
- Custom default file

Security

- 802.1x
- 802.1pq
- Transport Layer Security (TLS)
- AES encryption of config file for provisioning (128/64/32/16 bits)
- LLDP-MED

Network

- STUN
- NAT
- RTP, SRTP
- SNTP
- VLAN
- Failover support and server redundancy
- Layer 3 QoS (ToS, Diffserv)

Voice Codec

- G.711 a-law & u-law
- G.722
- G.726
- G.729

Provisioning

- HTTP, HTTPS, FTP, TFTP
- DHCP options: 66, 159, 160
- PnP

Maintenance

- Diagnostic: pcap trace
- Schedule resync: time and day setting
- Syslog

Compatibility

- Broadsoft Broadworks®
- Asterisk-based platforms
- Metaswitch Networks
- Genband™

Other

- 3-year standard warranty
- Optional AC adapter: VSP715-ADPT
- Advanced product replacement for warranty claims with new product



Pulse Supply
909 Ridgebrook Road.
Sparks, Maryland 21152, USA

TEL : +1-410-583-1701
FAX : +1-410-583-1704
E-mail: sales@pulsesupply.com
<https://www.pulsesupply.com/vtech>

